



Compressible Joint Filler
if applicable the fire resistance
to be specified

Head Restraint
Sliding Anchor Fixing
e.g Ancon IHR-V,
fixed to Concrete Soffit

Blocks from Lignacite Ltd -
type and finish to be specified

10-12mm

Concrete Floor Slab

REV.	DATE.	DESCRIPTION.	BY.

These details have been produced for guidance only. It is the responsibility of the building designer to ensure that the details shown are compatible with the overall building design and will satisfy the relevant parts of the Building Regulations applicable before they are adopted into the project design.

LIGNACITE

Concrete Masonry Products

Lignacite Ltd
Norfolk House, High St
Brandon, Suffolk IP27 0AX.

Tel : +44 (0)1842 810678
Fax : +44 (0)1842 814602
E-mail : info@lignacite.co.uk

Concrete Blockwork

Head Restraint to a Concrete Floor
allowing for Vertical Deflection

DWG No. TDS/09

DRAWN BY PTS CHECKED BY C.M.

DATE June 2016 SCALE 1:5 @ A4 REV.NO.

Notes.

1. A nominal gap of 10-12mm is assumed between top of blockwork and concrete floor. However, this will need to be confirmed to suit the anticipated floor deflection.

2. Head restraints fixed typically at 450mm or 900mm centres as advised by project engineer.