



DECLATION OF PERFORMANCE

1 Unique identification code of the product

type:

2 Intended use/es: Loadbearing and non-loadbearing walls

3 Manufacturer Lignacite Ltd,

Norfolk House, High Street

Brandon, Suffolk,

Fibo 3.6N 140

IP27 OAX

4 Authorised Representative: Not Applicable

5 System's of AVCP: System 2+

6 Designated Standard: BS EN 771-3:2011+A1:2015

Approved Body: BSI

Approved Body Number: 0086

7 Declared Performances:

Essential Characteristics		Performance		
	Length (mm)	440		
Dimensions:	Width (mm)	140		
	Height (mm)	215		
	Tolerance Category	D1		
Configuration		Group 1		
	Mean Strength (N/mm²)	3.6		
Compressive Strength	Direction of Load	Perpendicular to the bed face		
	Unit Category	Category I		
Moisture Movement (mm/m)		<0.6		
Shear Bond Strength (N/mm²)		0.15 (Tabulated Value)		
Flexural Bond Strength (N/mm²)		No Performance Determined		
Reaction To Fire		Euroclass A1		
Water Absorption by Capillarity		No Performance Determined		
Water Vapour Permeability (μ)		5/15		
Direct Airborne Sound Insulation	Gross Density (kg/m³)	850		
	Configuration: Dimension and Tolerances	Group 1		
Thermal Conductivity W/mK (λ, _{10,dry})		0.24		
Thermal Resistance m ² K/W		0.58		
Durability Against Freeze-Thaw		Frost Resistant (Refer to Product Data Sheet)		
Dangerous Substances		No Performance Determined		

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 [as it has effect in the United Kingdom in respect of Great Britain], under the sole responsibility of the manufacturer.

Signed on behalf of		Date:	11/07/2025
Lignacite Ltd.	WE	Date:	11/0//2025

Marvyn Candler / SHEQ Manager Brandon, Suffolk, UK

Category: Quality	Type: Declaration of Pe	Type: Declaration of Performance		Reference: DOP-LIG-011	
Page 1 of 1	Issue Date: 11/07/2025	Issue No.: 001	Public	Author: Marvyn Candler	