



DECLATION OF PERFORMANCE

1 Unique identification code of the product

type:

Lignacite GP 7.3N 140

2 Intended use/es: Load bearing and non-load bearing walls and floors

3 Manufacturer Lignacite Ltd,

Norfolk House, High Street

Brandon, Suffolk,

IP27 OAX

4 Authorised Representative: Not Applicable

5 System's of AVCP: System 2+

6 Designated Standard: BS EN 771-3:2011+A1:2015

Approved Body: BSI

Approved Body Number: 0086

7 Declared Performances:

Essential Characteristics		Performance	
Dimensions:	Length (mm)	440	
	Width (mm)	140	
	Height (mm)	215	
	Tolerance Category	D1	
Configuration		Group 1	
Compressive Strength	Mean Strength (N/mm²)	7.3	
	Direction of Load	Perpendicular to the bed face	
	Unit Category	Category I	
Moisture Movement (mm/m)		<0.5	
Shear Bond Strength (N/mm²)		0.15 (Tabulated Value)	
Flexural Bond Strength (N/mm²)		No Performance Declared	
Reaction To Fire		Euroclass A1	
Water Absorption by Capillarity		No Performance Determined	
Water Vapour Permeability (µ)		5/15	
Direct Airborne Sound Insulation	Gross Density (kg/m³)	1450	
	Configuration: Dimension and Tolerances	Group 1	
Thermal Conductivity W/mK (λ, _{10,dry})		0.42	
Thermal Resistance m² K/W		0.33333	
Durability Against Freeze-Thaw		Frost Resistant (Refer to Product Data Sheet)	
Dangerous Substances		No Performance Determined	

The performance of the product identified above is in conformity with the declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 [as it has effect in the United Kingdom in respect of Great Britain], under the sole responsibility of the manufacturer.

Signed on behalf of Lignacite Ltd. Date: 11/07/20
--

Marvyn Candler / SHEQ Manager Brandon, Suffolk, UK

Category: Quality	Type: Declaration of Pe	Type: Declaration of Performance		Reference: DOP-LIG-005	
Page 1 of 1	Issue Date: 11/07/2025	Issue No.: 001	Public	Author: Marvyn Candler	