

DECLARATION OF PERFORMANCE

- | | | |
|----------|--|---|
| 1 | Unique identification code of the product type: | Lignacite Standard 7.3N 140 |
| 2 | Intended use/es: | Load bearing and non-load bearing walls and floors |
| 3 | Manufacturer | Lignacite Ltd,
Norfolk House, High Street
Brandon, Suffolk,
IP27 0AX |
| 4 | Authorised Representative: | Not Applicable |
| 5 | System's of AVCP: | System 2+ |
| 6 | Designated Standard: | BS EN 771-3:2011+A1:2015
Approved Body: BSI
Approved Body Number: 0086 |
| 7 | Declared Performances: | |

Essential Characteristics		Performance
Dimensions:	Length (mm)	440
	Width (mm)	140
	Height (mm)	215
	Tolerance Category	D1
Configuration		Group 1
Compressive Strength	Mean Strength (N/mm ²)	7.3
	Direction of Load	Perpendicular to the bed face
	Unit Category	Category I
Moisture Movement (mm/m)		<0.7
Shear Bond Strength (N/mm ²)		0.15 (Tabulated Value)
Flexural Bond Strength (N/mm ²)		No Performance Determined
Reaction To Fire		Euroclass A1
Water Absorption by Capillarity		No Performance Determined
Water Vapour Permeability (μ)		5/15
Direct Airborne Sound Insulation	Gross Density (kg/m ³)	1450
	Configuration: Dimension and Tolerances	Group 1
Thermal Conductivity W/mK (λ _{10,dry})		0.79
Thermal Resistance m ² K/W		0.17722
Durability Against Freeze-Thaw		Frost Resistant (Refer to Product Data Sheet)
Dangerous Substances		No Performance Determined

The performance of the product identified above is in conformity with the declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 *[as it has effect in the United Kingdom in respect of Great Britain]*, under the sole responsibility of the manufacturer.

Signed on behalf of Lignacite Ltd.		Date:	11/07/2025
---------------------------------------	---	--------------	------------

Marvyn Candler / SHEQ Manager
Brandon, Suffolk, UK